

Directional spool valves
hand lever operated type WMM6
rotary knob operated type WMD6
roller operated type WMR6
hydraulically operated type WH6

NS6

up to 31,5 MPa

up to 80 dm³/min

11.2015

DATA SHEET - OPERATION MANUAL

APPLICATION

Directional spool valves are intended for change in direction of fluid flow in a hydraulic system and thus it allows to change direction of movement of a receiver - mostly piston rod of a cylinder or hydraulic motor as well to use functions: *on* and *off*.

Directional spool valves can be made in differently operated design versions:

- hand lever operated type **WMM6**
- rotary knob operated type **WMD6/WMDA6**
- roller operated type **WMR6/WMU6**
- hydraulically operated type **WH6**

These directional valves are intended for subplate mounting in any position in hydraulic system.



DESCRIPTION OF OPERATION


General information

Main bore and annular ports **P**, **T**, **A**, **B** are made in the housing (1) and are connected to its subplate connection.

Directional valve is switched by shifting the spool (2) into one end position. Various control functions are dependent on shape of the spool (2), which affects the change in configuration of connections among ports **P**, **T**, **A**, **B** in the housing (1).

Directional spool valve - hand lever operated type WMM6


The spool (2) is shifted as a result of changing position of the hand lever (3), by means of pin (4). The spool return (2) to its rest is secured by springs (6) - version ...WMM6.../... or the spool (2) is positioned by means of the detent (5) - versions ...WMM6.../F. Directional spool valve may be equipped with throttle insert (7) placed in port **P** - version WMM6.../...B.



DESCRIPTION OF OPERATION


Directional spool valve - rotary knob operated type WMD6, WMDA6

The spool (2) is shifted by means of rotary knob (3) through the spindle (4) and by means of the spring (6). The spool is positioned by means of detent (5). Directional spool valve may be provided with orifice (7) placed in port P - version ...WMD6.../FB.




Directional spool valve - roller operated type WMR6/WMU6

The spool (2) is shifted by means of the pin (3) with the roller (4) at the end of pin, through the plunger (5). Spool return (2) to its rest position is secured by the spring (6). Directional spool valve may be provided with orifice (7) placed in port P - version ...WMR.../B.



Directional spool valve -hydraulically operated type WH6

The spool (2) is shifted by means of the pressure supplied to connections of the caps (3) and thus it allows to move spools (4). Spool return (2) and its centering in neutral position (3-position directional valves) or fixing end positions (2-position directional valves) is secured by the springs (5) - version ...WH6...-12/...; hydraulically (with oil pressure) - version ...WH6.../O... or by means of detent - version ...WH6.../OF.... In versions: ...WH6.../O... and ...WH6.../OF... the spool position (4) is not fixed in case of the lack of supply. Directional spool valve may be provided with orifice (6) placed in port P - version ...WH6.../...B.



TECHNICAL DATA

Hydraulic fluid	mineral oil							
Required fluid cleanliness class	ISO 4406 class 20/18/15							
Nominal fluid viscosity	37 mm ² /s at temperature 55 °C							
Viscosity range	2,8 up to 380 mm ² /s							
Fluid temperature range (in a tank)	recommended	40°C up to 55°C						
	max	-20°C up to +70°C						
Ambient temperature range	- 20°C up to +70°C							
Features	type WMM6		type WMD6/WMDA6		type WMR6/WMU6		type WH6	
Max operating pressure	ports		ports		ports		ports	
	P, A, B	T	P, A, B	T	P, A, B	T	P, A, B	T
	31,5 MPa	16 MPa	31,5 MPa	16 MPa	31,5 MPa	6 MPa	31,5 MPa	16 MPa
Control pressure	—		—		—		min 0,6 - 1 MPa	
							max 20 MPa	
Switching force	pressure in port T				100 - 200 N			
	0 MPa	15 MPa	—				—	
	~ 20 N	~ 30 N						
Tightening torque of rotary knob	—		150 Ncm		—		—	
Max angle of control cam	—		—		30°		—	
Weight	1,4 kg		1,4 kg		1,4 kg		version with 2 control ports 1,8 kg	
							version with 1 control port 1,3 kg	
Flow section in θ (central) position	spool Q - 6 % nominal section spool W - 3 % nominal section							


INSTALLATION AND OPERATION REQUIREMENTS

- | | |
|---|---|
| <ol style="list-style-type: none"> 1. Only fully functional and operational valve must be used. 2. During the period of operation must be kept fluid viscosity acc. to requirements defined in this Data Sheet - Operation Manual 3. In order to ensure failure free and safe operation the following must be checked: <ul style="list-style-type: none"> • proper working of the valve • cleanliness of the hydraulic fluid 4. Due to heating of valve body to high temp., the valve shall be placed in such way to eliminate the risk of | <ol style="list-style-type: none"> 5. In order to ensure tightness of the directional valve block, one should take care of dimension of sealing rings and valve operation parameters given in this Data Sheet - Operation Manual 6. A person that operates the valve must be thoroughly familiar with this Data Sheet - Operation Manual. <p>accidental contact with the valve body during operation or to apply suitable covers acc. to PN - EN ISO 13732 - 1 and PN - EN 4413</p> |
|---|---|

DIAGRAMS


Directional spool valve - hand lever operated type ...WMM6...-3X/...

Graphic symbols of 3-position directional spool valves




Graphic symbols of 2-position directional spool valves

versions with positions a, 0



versions with positions 0, b



Graphic symbols of spools

working and indirect positions


working positions

working and indirect positions

working positions

working and indirect positions

working positions





NOTES:

Flow sections in 0 (central) position achieved with spools:
Q and W - according to technical data on page 3.

DIAGRAMS



Directional spool valve - hand lever operated type ...WMM6...-3X/...

Graphic symbols of 2-position
directional spool valves





Graphic symbols of spools

working
and indirect
positions



working
positions






A




C

D

working
and indirect
positions



working
positions




B

Y

Directional spool valve - rotary knob operated type ...WMD6...-3X/... ; ...WMDA6...-3X/...



Graphic symbols of 2-position
directional spool valves

versions with positions a, b






Graphic symbols of spools

working
and indirect
positions



working
positions



A


C

D



DIAGRAMS

Directional spool valve - rotary knob operated type ... WMD6...-3X/... ; ...WMDA6...-3X/...

Graphic symbols of 3-position directional spool valves



Graphic symbols of 2-position directional spool valves



Graphic symbols of spools

working and indirect positions







working positions

working and indirect positions



working positions

working and indirect positions



working positions





E




EA





EB





F




FA





FB




G




GA





GB



H




HA



HB



J




JA




JB




L




LA



LB



M





MA



MB





P




PA





PB




Q




QA





QB




R





RA




RB



T




TA





TB



U





UA




UB





V



VA



VB



W



WA



WB


NOTES:

Flow sections in 0 (central) position achieved with spools:
Q and W - according to technical data on page 3.


DIAGRAMS

Directional spool valve - roller operated type ...WMR6...-3X/... ; ...WMU6...-3X/...

Graphic symbols of 3-position
directional spool valves











Graphic symbols of 2-position
directional spool valves









Graphic symbols of spools

working
and indirect
positions




working
positions



Graphic symbols of spools

working
and indirect
positions



working
positions




NOTES:

Flow sections in 0 (central) position achieved with spools:
Q and W - according to technical data on page 3.

DIAGRAMS


Directional spool valve - hydraulically operated type ...WH6...-3X/...

Graphic symbols of 3-position
directional spool valves




Graphic symbols of 2-position
directional spool valves

versions with positions a, 0



versions with positions 0, b



Graphic symbols of spools

working
and indirect
positions









working
positions

working
and indirect
positions


working
positions

working
and indirect
positions



working
positions





E




EA




EB





F




FA





FB





G




GA





GB



H



HA



HB




J



JA




JB




L




LA





LB




M





MA




MB



P





PA





PB



Q





QA



QB



R




RA




RB



T





TA




TB



U




UA




UB




V




VA





VB



W



WA



WB

NOTES:


Flow sections in 0 (central) position achieved with spools:
Q and W - according to technical data on page 3.

DIAGRAMS


Directional spool valve - hydraulically operated type ...WH6...-3X/...

Graphic symbols of 2-position directional spool valves

versions with positions a, b





versions with positions a, b





Graphic symbols of spools



working and indirect positions





working positions



working and indirect positions






working positions



OVERALL AND CONNECTION DIMENSIONS


Directional spool valve - hand lever operated
type ...WMM6...-3X/...



- 1 - Hand lever
- 2 - Sealing o-ring 9,2 x 1,8 - 4 pcs/set (P,T,A,B)
- 3 - Overall dimension of directional spool valve:
 - 3-position directional spool valve springs centered
 - 3-position directional spool valve positioned with detent (spool diagrams: E,F,G,H,I,J,L,M,Q,R,T,U,V,W - according to page 4)
 - 2-position directional spool valve positioned with return spring
 - 2-position directional spool valve positioned with detent (positions a, 0 - spool diagrams: EA,FA,GA,HA,JA,LA,MA,PA,QA,RA,TA,UA,VA,WA - according to page 4) (positions 0, b - spool diagrams: EB,FB,GB,HB,JB,LB,MB,PB,QB,RB,TB,UB,VB,WB - according to page 4) (positions a, b - spool diagrams: A,C,D,B,Y- according to page 5)
- 4 - Positions of hand lever for different versions of directional spool valves
- 5 - Porting pattern - configuration of connection holes in subplate in accordance with the standard ISO 4401 designation ISO 4401-03-02-0-94 (CETOP 03) fixing screws M5 x 50 -10.9 in accordance with PN - EN ISO 4762 - 4 pcs/set - must be ordered separately; tightening; torque Md = 9 Nm
- 6 - Subplate surface required

OVERALL AND CONNECTION DIMENSIONS



Directional spool valve - rotary knob operated
type ... WMD6...-3X/... ; ...WMDA6...-3X/...



- 1 - Rotary knob
- 2 - Sealing o-ring 9,2 x 1,8 - 4 pcs/set (P,T,A,B)
- 3 - Overall dimension - version WMD6...
- 4 - Overall dimension - version WMDA6...
- 5 - Stroke of rotary knob for 3-position directional valve (spools diagrams: E,F,G,H,I,L,M,Q,R,T,U,V,W - page 6)
- 6 - Stroke of rotary knob for 2-position directional valve (positions a, 0 - spools diagrams: EA,FA,GA,HA, JA, LA, MA,PA,QA,RA,TA,UA,VA,WA - page 6, positions a, b - spools diagrams: A,C,D - page 5)
- 7 - Stroke of rotary knob for 2-position directional valve (positions 0, b - spools diagrams: EB,FB,GB,HB,JB, LB, MB,PB,QB,RB,TB,UB,VB,WB - page 6)
- 8 - Positions of rotary knob for different versions of directional spool valve
- 9 - Porting pattern - configuration of connection holes in subplate in accordance with the standard ISO 4401 designation ISO 4401-03-02-0-94 (CETOP 03) fixing screws M5 x 50 -10.9 in accordance with PN - EN ISO 4762 - 4 pcs/set - must be ordered separately; tightening torque Md = 9 Nm
- 10 - Subplate surface required

OVERALL AND CONNECTION DIMENSIONS



Directional spool valve - roller operated
 type ... WMR6...-3X/... ; ...WMU6...-3X/...



- 1 - Pin with roller - position for valve type **WMR6**...
- 2 - Pin with roller - position for valve type **WMU6**...
- 3 - Sealing ring **o-ring 9,2 x 1,8** - 4 pcs/set (P,T,A,B)
- 4 - Overall dimension of directional spool valve:
 - type **WMR6**... (2 and 3-position versions)
 - type **WMU6**... (2 and 3-position versions)
- 5 - Stroke of roller for **3-position directional spool valve** (spools diagrams: E,F,G,H,J,L,M,Q,R,T,U,V,W - page 7)
- 6 - Stroke of roller for **2-position valve** (spools diagrams: A,C,D - page 7)
- 7 - Max angle of control cam
- 8 - Position of pin with roller for different versions of directional valves (type **WMR6**... and **WMU6**...)
- 9 - Porting pattern - configuration of connection holes in subplate in accordance with the standard **ISO 4401** designation **ISO 4401-03-02-0-94 (CETOP 03)** fixing screws **M5 x 50 -10.9** in accordance with **PN - EN ISO 4762** - 4 pcs/set - must be ordered separately; tightening torque **Md = 9 Nm**
- 10 - Subplate surface required

OVERALL AND CONNECTION DIMENSIONS

Directional spool valve - hydraulically operated
type ...WH6...-3X/...




- 1 - Cap with control port **a**
- 2 - Cap with control port **b**
- 3 - Sealing **o-ring 9,2 x 1,8** - 4 pcs/set (P,T,A,B)
- 4 - Overall dimension of directional spool valve:
 - **3-position directional spool valve springs centered d** (spools diagrams: E,F,G,H,J,L,M,Q,R,T,U,V,W - page 8)
 - **2-position directional spool valve without return springs and without detent**
 - **2-position directional spool valve without return springs with detent** (positions: **a, b** - spools diagrams: A,C,D - page 9)
- 5 - Overall dimension of directional spool valve:
 - **2-position directional spool valve spring positioned** (positions **a, b** - spools diagrams: A,C,D - page 9; positions: **a, 0** - spools diagrams: EA,FA,GA,HA,JA,LA,MA,PA,QA,RA,TA,UA,VA,WA - page 8)
- 6 - Overall dimension of directional spool valve:
 - **2-position directional spool valve spring positioned** (positions: **a, b** - spools diagrams: B, Y - page 9; positions: **0, b** - spools diagrams: EB,FB,GB,HB,JB,LB,MB,PB,QB,RB,TB,UB,VB,WB - page 8)
- 7 - Porting pattern - configuration of connection holes in subplate in accordance with the standard **ISO 4401** designation **ISO 4401-03-02-0-94** (CETOP 03) fixing screws **M5 x 50 - 10.9** in accordance with **PN - EN ISO 4762** - 4 pcs/set - must be ordered separately; tightening torque **Md = 9 Nm**
- 8 - Subplate surface required

PERFORMANCE CURVES

measured at viscosity $\nu = 41 \text{ mm}^2/\text{s}$ and temperature $t = 50^\circ\text{C}$

Flow resistance curves

- type WMM6...; WMM6.../F...
- type WMD6.../F...; WMDA6.../F...
- type WMR6...; WMU6...
- type WH6...; WH6.../O...; WH6.../OF...




	A	B	C	D	E	F	G	H	J	L	M	P	Q	R	T	U	V	W	Y
P - A	3	3	1	5	3	2	5	2	1	1	2	2	1	5	5	3	1	1	5
P - B	3	3	1	5	3	3	3	4	1	1	4	3	1	5	3	1	2	1	5
A - T	-	-	3	3	1	3	6	2	2	2	3	3	2	4	6	3	1	2	3
B - T	-	-	1	3	1	5	6	2	1	2	3	5	1		6	3	1	2	3

Operating limits curves

- type WMM6 ...

Flow curves $p-Q$ for directional spool valve type WMM6 ... - versions with various spools springs centered



1	2	3	4	5
E1, M, E, J, L, Q, U, W, C, D, Y, G, H, R	A, B	V	F, P	T


PERFORMANCE CURVES

measured at viscosity $\nu = 41 \text{ mm}^2/\text{s}$ and temperature $t = 50^\circ\text{C}$

Operating limits curves

- type WMM6.../F...


Flow curves p - Q for directional spool valve type WMM6.../F... - versions with various spools positioned with detent



1	2	3	4	5	6	7	8	9
E1, M, H, C, D, Y	E, J, Q, L, U, W	A, B	G, T	F	V	P	R	T

- type WMD6.../F...
- type WMDA6.../F...

Flow curves p - Q for directional spool valve type: WMD6.../F...; WMDA6.../F... versions with various spools positioned with detent



1	2	3	4	5	6	7	8
E1, M, H, C, D, E, Q, U, W	J, L	A	G, P	F	V	R	T




PERFORMANCE CURVES

measured at viscosity $\nu = 41 \text{ mm}^2/\text{s}$ and temperature $t = 50^\circ\text{C}$

Operating limits curves

- type WMR6...
- type WMU6...




Flow curves p-Q for directional spool valve type: WMR6...; WMU6... - versions with various spools springs centered



1	2	3	4	5	6	7	8
A	C, D, E, E1, H, M, Q, U, W	F, P	G	J, L	R	T	V

- type WH6...
- type WH6.../O...
- type WH6.../OF...

Flow curves p-Q for directional spool valve type: WH6 ...; WH6.../O...; WH6.../OF... versions with spools springs centered, positioned with detent and without detent



p = 0,6 MPa		p = 1 MPa	
1	A, B	1	A, B
2	C, D, Y	8	C, D, Y, E, G, H, J
3	E, J, L, U, M, Q, V, W	8	L, U, M, Q, V, W
4	F, E	9	F, P
5	T	10	R
6	G, H	11	T
7	P	-	-
8	A/O, C/O, D/O	8	A/O, C/O, D/O, A/OF, C/OF, D/OF

HOW TO ORDER

		6	+	/			*
--	--	----------	---	---	--	--	---

Number of service ports

3-way - for spools A, B = **3**
4-way - for the other spools = **4**

Type of operation

hand lever operated = **WMM**
 rotary knob operated = **WMD**
 lockable rotary knob operated = **WMDA**
 roller operated (roller positioning according to page12) = **WMR**
 roller operated (roller positioning according to page12) = **WMU**
 hydraulically operated = **WH**

Nominal size (NS)

NS6 = **6**

Spool type

spool diagrams for directional spool valve:

type **WMM** - according to page **4, 5**
 type **WMD/WMDA** - according to page **5, 6**
 type **WMR/ WMU** - according to page **7**
 type **WH** - according to page **8, 9**

Series number

(30-39) - connection and installation dimensions unchanged = 3X
series 32 = **32**

Spool positioning

spring centering - possible for directional spool valves type: **WMM, WMR/WMU, WH** = **no designation**
with detent - possible for directional spool valves type: **WMM, WMD/WMDA** = **F**
 without return springs, without detent - possible for directional spool valves type WH = **0**
 without return springs, with detent - possible for directional spool valves type WH = **OF**

Throttle insert (in port P)

without throttle insert = **no designation**
 throttle insert ϕ 0,8 = B 08
 throttle insert ϕ 1,0 = B 10
 throttle insert ϕ 1,2 = B 12

Sealing

NBR (for fluids on mineral oil base) = **no designation**
 FKM (for fluids on phosphate ester base) = **V**

Further requirements in clear text (to be agreed with the manufacturer)

Directional spool valve should be ordered according to the above coding.

The symbols in bold are preferred versions in short delivery time.

Coding examples: 4WMM6 E -32/B08; 4WMD6 E -32/F B08; 4WMR6 E -32/B08; 4WH6 E -32/B08

SUBPLATES AND FIXING SCREWS

Subplates must be ordered according to the data sheet
WK 496 480. Subplates:

G 341/01 - threaded connection G 1/4

G 342/01 - threaded connection **G 3/8**

G 502/01 - threaded connection G1/2

G 341/02 - threaded connection M14 x1,5

G 342/02 - threaded connection M16 x1,5


Subplates and fixing screws M5 x 50 - 10,9 - 4 pcs/set
must be ordered separately.

Tightening torque for screws $Md = 9 \text{ Nm}$


Subplate symbol in bold is the preferred version available in short delivery time.

EXAMPLES OF APPLICATION IN HYDRAULIC SYSTEM

**Directional spool valve - hand lever operated
type WMM6**



**Directional spool valve - hydraulically operated
type WH6**



PONAR Wadowice S.A.
ul. Wojska Polskiego 29
34-100 Wadowice
tel. +48 33 488 21 00
fax. +48 33 488 21 03
www.ponar-wadowice.pl

PONAR[®]
wadowice